

Trace Matcher - Feature #10099

"--start-addr <hex value>" command line option

02/05/2020 02:07 PM - Sergey Smolov

Status:	Resolved	Start date:	02/05/2020
Priority:	Normal	Due date:	
Assignee:	Sergey Smolov	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	0.1		
Published in build:			

Description

The option specifies an address of instruction record from particular trace from which the comparison of the trace should be started.

If the option is not specified, the comparison process should start from the first records of traces.

If the option is specified, but an instruction record has not been found at the *part of the trace to be processed* (all trace, by default), an error is returned.

Associated revisions

Revision 0b090666 - 02/06/2020 11:40 AM - Sergey Smolov

PyGradle-based build system, '--start-addr' option (#10099)

Signed-off-by: Sergey Smolov <smolov@ispras.ru>

Revision ae4dad37 - 02/07/2020 01:15 PM - Sergey Smolov

'--start-addr' option (#10099), refactoring

Signed-off-by: Sergey Smolov <smolov@ispras.ru>

Revision 1415183e - 02/07/2020 03:49 PM - Sergey Smolov

fix to '--start-addr' (#10099)

Signed-off-by: Sergey Smolov <smolov@ispras.ru>

History

#1 - 02/07/2020 02:06 PM - Sergey Smolov

- % Done changed from 0 to 100

- Status changed from New to Resolved

Done in [ae4dad37](#)